



ARKOS FLEETMAX 1000 20W-40 Diesel Engine Oil

ARKOS FLEETMAX 1000 20W-40 is a multi-grade Diesel engine oil formulated with high quality base oils and excellent detergent and dispersant properties that minimize deposits because of excellent sludge and varnish control. The Engine oil is formulated to provide good excellent wear protection.

Benefits

- ARKOS FLEETMAX 1000 20W-40 has a high Viscosity Index which ensures that it is free-flowing when cold and maintains high viscosity when hot. The choice of viscosity grade depends on climatic conditions and on the manufacturer's recommendations.
- Its detergent-dispersant properties minimize the formation of lacquer and varnish, as well as sludge and other engine deposits, help prevent ring sticking and keep pistons clean, while maintaining potential deposits in suspension.
- ARKOS FLEETMAX 1000 20W-40 resists deterioration, especially that caused by oxidation due to prolonged high-temperature operation in the presence of air and other agents.
- Its anticorrosion properties effectively protect the engine from corrosion by combustion moisture and acids.
- Its anti-wear properties ensure long life of moving parts and reduce the need for engine servicing and overhauls.
- Its antifoam properties prevent the formation of air bubbles which could adversely affect lubricant film continuity.

Applications

Recommended for Diesel passenger cars, Commercial vehicles, Earth moving equipments, Tractors, etc., where a API CF-4 performance engine oil is recommended

Performance Specifications

ARKOS FLEETMAX 1000 20W-40 meets the requirements of the following specifications:

- API CF-4

Characteristics (Typical Values)

ARKOS FLEETMAX 1000 20W-40		
TEST PARAMETERS	METHOD	TYPICAL VALUES
Viscosity at 100°C	mm ² /s	14.40
Viscosity Index	-	127
Flash Point COC	°C	> 220
Pour Point	°C	< -21
Density @29.5°C	gms/cc	0.87

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your particular vehicle/machine/equipment.



Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: